

## General Data

|  |                                    |  |                                   |
|--|------------------------------------|--|-----------------------------------|
| <b>Product name</b><br>Streamer  | <b>Article. No.</b><br>80300-80311 | <b>Suffix no.</b><br>,-543                   |                                   |
| <b>Contact person, tel., e-mail</b><br>Niclas Thulin, +46 36 2906169<br>niclas.thulin@fagerhult.se |                                    | <b>Declaration established</b><br>2022-06-07 | <b>Last updated</b><br>2022-06-07 |

## Supplier Information

|  |  |
|--|--|
| <b>Company information</b>   |  |
| Fagerhults Belysning AB<br>SE-566 80 Habo, SWEDEN<br>Org nr 5563218659   | Tel: +46 36-10 85 00<br><a href="http://www.fagerhult.com">www.fagerhult.com</a> |
| <b>Company description</b>   |  |
| Fagerhult develops, manufactures and markets professional lighting systems for public environments such as offices, schools, hospitals and industries. |  |
| <b>Certifications</b>  |  |
| Fagerhult is certified according to ISO 14001 och ISO 9001   |  |

## Legal requirements regarding the product

|   |
|---|
| <p>If the product contains &gt;0,1 % by weight of substances that are listed on the candidate list within Reach, this is presented in the comments below.</p> <p>The product fulfills Low Voltage-, EMC- and RoHS-directives. Fagerhult is associated with national systems for recycling of electric and electronic waste and the luminaire is recyclable to &gt;90% if it is treated as electrical waste at end of life. Fagerhult is also connected to national packaging recycling systems, therefore we comply with the WEEE and packaging directives.</p> |
|---|

## Structure and content

| Material content          | CAS no. / Reference | % by weight | Comments               |
|---------------------------|---------------------|-------------|------------------------|
| Aluminium                 | ADC12               | < 62,3      |                        |
| Driver                    |                     | < 14,8      | Electronics in driver  |
| Plastic – PC              |                     | < 15        | Driver/adapter housing |
| Carbon steel              | 1022A               | < 2,9       |                        |
| Copper                    |                     | < 2,7       |                        |
| Aluminium                 | 1090                | < 2,5       |                        |
| Plastic – ABS             |                     | < 1,4       |                        |
| Plastic – PBT             |                     | < 0,7       |                        |
| COB (LED) – Ceramic based |                     | < 0,4       |                        |
| Glass fibre               |                     | < 0,3       | sleeve                 |
| Powder coating            | Epoxy/polyester     | < 0,3       |                        |
| Contact paste             |                     | < 0,2       |                        |
| Plastic – FEP             |                     | < 0,2       | Cable insulation       |
| Plastic – PFTE            |                     | < 0,1       |                        |

## Transports and packing

|  |
|--|
| Transports are mainly done by trucks. Product is packed with corrugated cardboard and/or plastic (PE & EPS). |
|--|

## Environmental impact within the life cycle

|  |
|--|
| The product's main environmental impact during its life cycle is the energy consumed during use. The product's end of life is estimated to 20 years. |
|--|